

20.1" RACK MOUNT LCD MONITOR



- 20.1" TFT LCD display with 1600 x 1200 resolution.
- Steel construction with a durable powder coat finish.
- Wide viewing angle offers mounting flexibility.
- Optional Lexan™ screen protection.
- Mounts in 8U of 19" rack space.
- Analog and Digital inputs.

GENERAL SPECIFICATIONS

Dimensions: 19.0" (W) x 14.0" (H) x 3.3" (D)

Weight:
18.0 lbs.

Power:
100 - 240 VAC, 50/60 Hz.
58 Watts typ.

On-Screen Controls:
Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Input Select, Color Temp., Reset.

Plug & Play:
DDC1 and DDC2B

Temperature:
Operating: 10°C to 40°C
Storage: -20°C to 45°C

Humidity:
Operating: 10 to 80% RH (max)

Input Signal (VGA):
R.G.B. analog video, TTL H & V sync.

Input Signal (Digital):
DVI-D (TDMS).

Input Connectors:
Analog: 15-pin mini D-Sub.
Digital: 24 pin DVI-D.

Colors Available:
Black.

DISPLAY SPECIFICATIONS

Display Type:
Active matrix TFT LCD

Display area:
20.1" Diagonal.

Colors Displayed:
16.7 million colors.

Contrast Ratio:
800:1

Brightness:
300 cd/m² typ.

Viewing Angle (CR>5):
Horizontal: 178° Vertical:
178°

Response Time:
8 ms GTG.

Resolution:
VGA up to 1600 x 1200.

Specifications subject to change without notice.

MODEL NUMBER

LTRM-420

LTRM-420L with Lexan™ screen protection.



Offering OEM and custom solutions.
Contact us for additional information.

LAN TEK 1-800-660-2286

www.lantekrackmount.com
lantek@earthlink.net

Tel: 760-364-2900 Fax: 760-364-4997
P. O. Box 549 Yucca Valley, CA 92286