

# 10.4" LCD RACK MOUNT MONITOR (4U)



- Provides big display features in a compact package.
- VGA, Composite, S-Video and stereo audio inputs.
- Supplied with VGA cable and AC/DC power adapter with power cord.
- Housed in rugged steel construction with a durable powder coat finish.
- Removable rack mounting brackets allow for additional mounting options.
- Integrated 4W speakers with separate power switch and volume control.

## GENERAL SPECIFICATIONS

### Dimensions:

19.0" (W) x 7.0" (H) x 2.5" (D)

### Weight:

8 lbs

### Power:

90 - 260 VAC, 50/60 Hz.  
60 Watts maximum

### On-Screen Controls:

Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Load and Save Values

### Plug & Play:

DDC1 and DDC2B

### Temperature:

Operating: 0°C to 50°C  
Storage: -20°C to 60°C

### Humidity:

Operating: 10 to 85% RH (max)

### Input Signal (VGA):

R.G.B. analog video, TTL H & V sync.

### Input Connectors:

Display: 15-pin mini D-Shell  
Composite Video - RCA  
S-Video - mini-DIN  
Audio: 3.5 mm Stereo Jack

### Colors Available:

Black(B).

## DISPLAY SPECIFICATIONS

### Display Type:

Active matrix TFT LCD

### Colors:

262K colors

### Contrast Ratio:

600:1 typ.

### Brightness:

190 cd/m<sup>2</sup> typ.

### Viewing Angle:

Horizontal: 178°  
Vertical: 178°

### Response Time:

25ms.

### Resolution:

640 x 350  
640 x 480  
800 x 600  
1024 x 768

### Horizontal Frequency:

31.5 to 80 KHz

### Vertical Frequency:

56 to 75 Hz.

### Surface Treatment:

Anti-glare/Hard coat (3H)

Specifications subject to change without notice.

## MODEL NUMBER

LTRM-710SV(X)

L = Lexan™ Screen Protection

Contact us about other options and our additional rack mount products.



Tel: 760-364-2900  
web: www.lan-tek.net, www.lantekrackmount.com  
P. O. Box 549

LAN TEK  
**1-800-660-2286**

Fax: 760-364-4997  
email: lantek@earthlink.net  
Yucca Valley, CA 92286